



- A Insulating grip see chart for color
- B Terminal male zinc alloy
- C Nominal current OCR font
- D Test points
- E Nominal voltage inmoulded

ELED ref.	RATING [A]	COLOR	VOLTAGE [V]
FLP7002	2	Gray	58
FLP7003	3	Violet	58
FLP7004	4	Pink	58
FLP7005	5	Tan	58
FLP7075	7,5	Brown	58
FLP7010	10	Red	58
FLP7015	15	Blue	58
FLP7020	20	Yellow	58
FLP7025	25	Natural	58
FLP7030	30	Green	58

FUSING TIME ISO 8820-9		
LOAD [%]	MIN [s]	MAX [s]
110	360.000	-
135	0,75	600
160	0,25	50
200	0,15	5
350	0,04	0,5
600	0,02	0,1

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: 0,2 LINEAR: ANGULAR:				FINISH:	DEBUR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
ELED						MICRO fuses family	
DRAWN	NAME	SIGNATURE	DATE	TITLE:			
	B.D.		12.2014	FLP7000			
CHK'D							
APPV'D							
MFG							
Q.A				MATERIAL:	DWG NO.	A4	
				WEIGHT:	SCALE:5:1	SHEET 1 OF 1	